

## PASSIVE SERIES

### [ Lansche Audio No.3 Loudspeaker ]

The No.3 loudspeaker is our entry level two-way all passive loudspeaker. But, don't be fooled by misconceptions; this speaker gives much more than you would expect from a two-way.

Featuring our legendary CORONA tweeter, a totally massless driver with a frequency range from 1.5kHz to 150kHz without resonances! No other tweeter in the world can approach the CORONA's sound and performance.

The mid-bass driver is one of a kind: exceptionally light and fast enough to 'keep up' with the Corona. Yet, strong and powerful enough to reproduce low frequencies with ease.

The quartz sand filled bass cabinet ensures resonances are kept to a minimum.

The crossover uses only high quality components which are externally damped by being submerged in quartz sand. As in all Lansche speakers, the internal wiring is silver plated OFC.

With a high efficiency of 91dB/1m it offers an easy match for amplifiers with 15 watts output power or more.

Cabinet finishes are in a range of high quality wood veneers. Available in matte or hand polished polyurethane lacquer.

All of this in a small elegant enclosure suitable for today's modern living requirements.

### Technical Specifications:

Description	2-way speaker with bass reflex port
Tweeter	1 x 8mm (0.3") CORONA plasma tweeter
Woofer	1 x 22cm (8.7") composite coated paper cone
Crossover frequency	2.5kHz
Impedance	8Ω, 4Ω minimum
Sensitivity	91 dB/1W/1m
Maximum level	106 dB/1m
Frequency Response	42 Hz to 150 kHz ±3dB
Internal wiring	Silver plated OFC
Weight	50 kg (110lbs)
Dimensions:	
Height	91.8 cms (36.2 in)
Width	23.5 cms (9.25 in)
Depth	38.0 cms (15.0 in)



[www.lansche-audio.com](http://www.lansche-audio.com)

